

## T-Strike Same as NOTE: Latch Center 1. Dimensions X and Y are variables dependent on door .313" (8) .625" (16) 2. Curved strike extension beyond jamb at Z must not be less than $\frac{3}{16}$ " (5) to ensure proper functioning of latch bolt 3. $1\frac{1}{8}$ " (29) Lip length for $1\frac{3}{8}$ " (35) to $1\frac{3}{4}$ " (44) doors. +.015 1.500<u></u> -.000 4. Strike location on frames must 2.750" 2.125" 1.313" be adjusted for thickness of +.015 +.015 (38) (33)door silencers, when used Lock -.000-.000Center (54) (70).625" (16).313" (8) .563" .563" (14) (14)1.125" +.015 -.000 Stop (29)Lip .125"±.005 (3) .687" **ORCA** (17)1.125" ±.005 Depth of Box (28)for Regular Latch Depth of Box Furnished for 3/4" (19) throw .875" .125" (3) Fire Door Latch (22)

## **Metal Jamb**

orcahardware.com

Jamb Type: Metal

Door Thickness: 1-3/8" (35mm) - 1-3/4" (45mm)
Description: T-Strike, Square Corner, No Box

Optional For: OCL200 Series Locks

Dimensions shown in parentheses () are in millimeters.

## RESPONSIBILITY

Door and Frame Manufacturers are responsible for providing adequate construction or reinforcements for proper installation of hardware shown. All architectural builders hardware must be installed on properly reinforced doors and frames, regardless of the type, material, or method of construction.

OCL Series T-Strike OCLTSK

## Orca Hardware

Do Not Scale Drawing		
Supersedes	Dr.	App.
Date 6-18	Template OCL	.TSKM